

**NEW SOURCE CONSTRUCTION PERMIT
and MINOR SOURCE OPERATING PERMIT
OFFICE OF AIR QUALITY**

**MTI Insulated Products, Inc.
4419 Ardmore Avenue
Fort Wayne, Indiana 46899**

(herein known as the Permittee) is hereby authorized to construct and operate subject to the conditions contained herein, the emission units described in Section A (Source Summary) of this permit.

This permit is issued to the above mentioned company under the provisions of 326 IAC 2-1.1, 326 IAC 2-5.1, 326 IAC 2-6.1 and 40 CFR 52.780, with conditions listed on the attached pages.

This permit is also issued under the provisions of 326 IAC 2-2, 40 CFR 52.21, and 40 CFR 52.124 (Prevention of Significant Deterioration), with conditions listed on the attached pages.

Operation Permit No.: MSOP 003-13570-00037	
Issued by: Paul Dubenetzky, Branch Chief Office of Air Quality Original Signed by Paul Dubenetzky	Issuance Date: April 26, 2001

TABLE OF CONTENTS

A SOURCE SUMMARY

- A.1 General Information [326 IAC 2-5.1-3(c)] [326 IAC 2-6.1-4(a)]
- A.2 Emission Units and Pollution Control Equipment Summary

B GENERAL CONSTRUCTION CONDITIONS

- B.1 Permit No Defense [IC 13]
- B.2 Definitions
- B.3 Effective Date of the Permit [IC 13-15-5-3]
- B.4 Revocation of Permits [326 IAC 2-1.1-9(5)]
- B.5 Modification to Permit [326 IAC 2]
- B.6 Minor Source Operating Permit [326 IAC 2-6.1]

C SOURCE OPERATION CONDITIONS

- C.1 PSD Minor Source Status [326 IAC 2-2]
- C.2 Preventive Maintenance Plan [326 IAC 1-6-3]
- C.3 Permit Revision [326 IAC 2-5.1-3(e)(3)] [326 IAC 2-6.1-6]
- C.4 Inspection and Entry [326 IAC 2-5.1-3(e)(4)(B)] [326 IAC 2-6.1-5(a)(4)]
- C.5 Transfer of Ownership or Operation [326 IAC 2-6.1-6(d)(3)]
- C.6 Permit Revocation [326 IAC 2-1-9]
- C.7 Opacity [326 IAC 5-1]
- C.9 Performance Testing [326 IAC 3-6]
- C.10 Compliance Monitoring [326 IAC 2-1.1-11]
- C.11 Monitoring Methods [326 IAC 3]
- C.12 Compliance Monitoring Plan - Failure to Take Response Steps [326 IAC 1-6]

Record Keeping and Reporting Requirements

- C.13 Malfunctions Report [326 IAC 1-6-2]
- C.14 Monitoring Data Availability [326 IAC 2-6.1-2] [IC 13-14-1-3]
- C.15 General Record Keeping Requirements [326 IAC 2-6.1-2]
- C.16 General Reporting Requirements [326 IAC 2-1.1-11] [326 IAC 2-6.1-2] [IC 13-14-1-13]
- C.17 Annual Notification [326 IAC 2-6.1-5(a)(5)]

D.1 EMISSIONS UNIT OPERATION CONDITIONS

Emission Limitations and Standards

- D.1.1 Volatile Organic Compounds (VOC) [326 IAC 8-2-12]
- D.1.2 Particulate Matter (PM) [326 IAC 6-3-2(c)]
- D.1.3 Preventive Maintenance Plan [326 IAC 1-6-3]

Compliance Determination Requirements

- D.1.4 Testing Requirements
- D.1.5 Volatile Organic Compounds (VOC)
- D.1.6 Volatile Organic Compounds (VOC)

Compliance Monitoring Requirements

- D.1.7 Particulate Matter (PM)
- D.1.8 Monitoring

Record Keeping and Reporting Requirements

- D.1.9 Record Keeping Requirements

TABLE OF CONTENTS (Continued)

Annual Notification Malfunction Report

SECTION A

SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in conditions A.1 through A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-5.1-3(c)] [326 IAC 2-6.1-4(a)]

The Permittee owns and operates a hydraulic lift equipment assembly plant.

Authorized Individual: Robert A. Fieldhouse, Vice President of Operations
Source Address: 4419 Ardmore Avenue, Ft. Wayne, Indiana 46899
Mailing Address: 4419 Ardmore Avenue, Ft. Wayne, Indiana 46899
Phone Number: (219) 479-4605
SIC Code: 3531
County Location: Allen
County Status: Attainment for all criteria pollutants
Source Status: Minor Source Operating Permit
Minor Source, under PSD

A.2 Emissions units and Pollution Control Equipment Summary

This stationary source is approved to construct and operate the following emissions units and pollution control devices:

- (a) One (1) paint booth equipped with four (4) air atomization spray guns used to paint mobile hydraulic lift equipment at a maximum capacity of 0.25 units per hour. Emissions are exhausted at four (4) stacks (identified as S-NW, S-NE, S-SW, and S-SE) with particulate matter controlled by four (4) dry filters.
- (b) One (1) assembly plant using organic solvent for hand wipe cleaning operations with maximum VOC emissions of 0.12 tons per year.

SECTION B GENERAL CONSTRUCTION CONDITIONS

THIS SECTION OF THE PERMIT IS BEING ISSUED UNDER THE PROVISIONS OF 326 IAC 2-1.1 AND 40 CFR 52.780, WITH CONDITIONS LISTED BELOW.

B.1 Permit No Defense [IC 13]

This permit to construct does not relieve the Permittee of the responsibility to comply with the provisions of the Indiana Environmental Management Law (IC 13-11 through 13-20; 13-22 through 13-25; and 13-30), the Air Pollution Control Law (IC 13-17) and the rules promulgated thereunder, as well as other applicable local, state, and federal requirements.

B.2 Definitions

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, any applicable definitions found in IC 13-11, 326 IAC 1-2, and 326 IAC 2-1.1-1 shall prevail.

B.3 Effective Date of the Permit [IC13-15-5-3]

Pursuant to IC 13-15-5-3, this permit becomes effective upon its issuance.

B.4 Revocation of Permits [326 IAC 2-1.1-9(5)]

Pursuant to 326 IAC 2-1.1-9(5)(Revocation of Permits), the Commissioner may revoke this permit if construction is not commenced within eighteen (18) months after receipt of this approval or if construction is suspended for a continuous period of one (1) year or more.

B.5 Modification to Permit [326 IAC 2]

Notwithstanding the Section B condition entitled "Minor Source Operating Permit", all requirements and conditions of this construction permit shall remain in effect unless modified in a manner consistent with procedures established for modifications of construction permits pursuant to 326 IAC 2 (Permit Review Rules).

B.6 Minor Source Operating Permit [326 IAC 2-6.1]

This document shall also become a minor source operating permit pursuant to 326 IAC 2-6.1 when, prior to start of operation, the following requirements are met:

- (a) The attached Affidavit of Construction shall be submitted to the Office of Air Quality (OAQ), Permit Administration & Development Section.
 - (1) If the Affidavit of Construction verifies that the facilities covered in this Construction Permit were constructed as proposed in the application, then the facilities may begin operating on the date the Affidavit of Construction is postmarked or hand delivered to IDEM.
 - (2) If the Affidavit of Construction does not verify that the facilities covered in this Construction Permit were constructed as proposed in the application, then the Permittee shall receive an Operation Permit Validation Letter from the Chief of the Permit Administration & Development Section prior to beginning operation of the facilities.
- (b) If construction is completed in phases; i.e., the entire construction is not done continuously, a separate affidavit must be submitted for each phase of construction. Any permit conditions associated with operation start up dates such as stack testing for New Source Performance Standards (NSPS) shall be applicable to each individual phase.
- (c) Upon receipt of the Operation Permit Validation Letter from the Chief of the Permit Administration & Development Section, the Permittee shall attach it to this document.

- (d) The operation permit will be subject to annual operating permit fees pursuant to 326 IAC 2-1.1-7(Fees).
- (e) Pursuant to 326 IAC 2-6.1-7, the Permittee shall apply for an operation permit renewal at least ninety (90) days prior to the expiration date established in the validation letter. If IDEM, OAQ, upon receiving a timely and complete permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect until the renewal permit has been issued or denied. The operation permit issued shall contain as a minimum the conditions in Section C and Section D of this permit.

SECTION C

SOURCE OPERATION CONDITIONS

Entire Source

C.1 PSD Minor Source Status [326 IAC 2-2] [40 CFR 52.21]

- (a) The total source potential to emit of all criteria pollutants is less than 250 tons per year. Therefore the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration) and 40 CFR 52.21 will not apply.
- (b) Any change or modification which may increase potential to emit to 250 tons per year from this source, shall cause this source to be considered a major source under PSD, 326 IAC 2-2 and 40 CFR 52.21, and shall require approval from IDEM, OAQ prior to making the change.
- (c) Any change or modification which may increase potential to emit to 10 tons per year of any single hazardous air pollutant, twenty-five tons per year of any combination of hazardous air pollutants, or 100 tons per year of any other regulated pollutant from this source, shall cause this source to be considered a major source under Part 70 Permit Program, 326 IAC 2-7, and shall require approval from IDEM, OAQ prior to making the change.

C.2 Preventive Maintenance Plan [326 IAC 1-6-3]

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMP) after issuance of this permit, including the following information on each emissions unit:
 - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions;
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.
- (b) The Permittee shall implement the Preventive Maintenance Plans as necessary to ensure that failure to implement the Preventive Maintenance Plan does not cause or contribute to a violation of any limitation on emissions or potential to emit.
- (c) PMP's shall be submitted to IDEM, OAQ, upon request and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ, may require the Permittee to revise its Preventive Maintenance Plan whenever lack of proper maintenance causes or contributes to any violation.

C.3 Permit Revision [326 IAC 2-5.1-3(e)(3)] [326 IAC 2-6.1-6]

- (a) The Permittee must comply with the requirements of 326 IAC 2-6.1-6 whenever the Permittee seeks to amend or modify this permit.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

Any such application should be certified by the “authorized individual” as defined by 326 IAC 2-1.1-1.

- (c) The Permittee shall notify the OAQ within thirty (30) calendar days of implementing a notice-only change. [326 IAC 2-6.1-6(d)]

C.4 Inspection and Entry [326 IAC 2-5.1-3(e)(4)(B)] [326 IAC 2-6.1-5(a)(4)]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee’s right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee’s premises where a permitted source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) Have access to and copy, at reasonable times, any records that must be kept under this title or the conditions of this permit or any operating permit revisions;
- (c) Inspect, at reasonable times, any processes, emissions units (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit or any operating permit revisions;
- (d) Sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) Utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

C.5 Transfer of Ownership or Operation [326 IAC 2-6.1-6(d)(3)]

Pursuant to [326 IAC 2-6.1-6(d)(3)] :

- (a) In the event that ownership of this source is changed, the Permittee shall notify IDEM, OAQ, Permits Branch, within thirty (30) days of the change.
- (b) The written notification shall be sufficient to transfer the permit to the new owner by an notice-only change pursuant to 326 IAC 2-6.1-6(d)(3).
- (c) IDEM, OAQ, shall issue a revised permit.

The notification which shall be submitted by the Permittee does require the certification by the “authorized individual” as defined by 326 IAC 2-1.1-1.

C.6 Permit Revocation [326 IAC 2-1-9]

Pursuant to 326 IAC 2-1-9(a)(Revocation of Permits), this permit to construct and operate may be revoked for any of the following causes:

- (a) Violation of any conditions of this permit.
- (b) Failure to disclose all the relevant facts, or misrepresentation in obtaining this permit.
- (c) Changes in regulatory requirements that mandate either a temporary or permanent reduction of discharge of contaminants. However, the amendment of appropriate sections of this permit shall not require revocation of this permit.

- (d) Noncompliance with orders issued pursuant to 326 IAC 1-5 (Episode Alert Levels) to reduce emissions during an air pollution episode.
- (e) For any cause which establishes in the judgment of IDEM, the fact that continuance of this permit is not consistent with purposes of this article.

C.7 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.8 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 6-4-2(4) is not federally enforceable.

Testing Requirements

C.9 Performance Testing [326 IAC 3-6]

- (a) Compliance testing on new emissions units shall be conducted within 60 days after achieving maximum production rate, but no later than 180 days after initial start-up, if specified in Section D of this approval. All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

no later than thirty-five (35) days prior to the intended test date. The Permittee shall submit a notice of the actual test date to the above address so that it is received at least two weeks prior to the test date.

- (b) All test reports must be received by IDEM, OAQ within forty-five (45) days after the completion of the testing. An extension may be granted by the IDEM, OAQ, if the source submits to IDEM, OAQ, a reasonable written explanation within five (5) days prior to the end of the initial forty-five (45) day period.

The documentation submitted by the Permittee does not require certification by the "authorized individual" as defined by 326 IAC 2-1.1-1.

Compliance Monitoring Requirements

C.10 Compliance Monitoring [326 IAC 2-1.1-11]

Compliance with applicable requirements shall be documented as required by this permit. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. All monitoring and record keeping requirements not already legally required shall be implemented when operation begins.

C.11 Monitoring Methods [326 IAC 3]

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, or other approved methods as specified in this permit.

C.12 Compliance Monitoring Plan - Failure to Take Response Steps [326 IAC 1-6]

- (a) The Permittee is required to implement a compliance monitoring plan to ensure that reasonable information is available to evaluate its continuous compliance with applicable requirements. This compliance monitoring plan is comprised of:
- (1) This condition;
 - (2) The Compliance Determination Requirements in Section D of this permit;
 - (3) The Compliance Monitoring Requirements in Section D of this permit;
 - (4) The Record Keeping and Reporting Requirements in Section C (Monitoring Data Availability, General Record Keeping Requirements, and General Reporting Requirements) and in Section D of this permit; and
 - (5) A Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. CRP's shall be submitted to IDEM, OAQ upon request and shall be subject to review and approval by IDEM, OAQ. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee and maintained on site, and is comprised of :
 - (A) Response steps that will be implemented in the event that compliance related information indicates that a response step is needed pursuant to the requirements of Section D of this permit; and
 - (B) A time schedule for taking such response steps including a schedule for devising additional response steps for situations that may not have been predicted.
- (b) For each compliance monitoring condition of this permit, appropriate response steps shall be taken when indicated by the provisions of that compliance monitoring condition. Failure to perform the actions detailed in the compliance monitoring conditions or failure to take the response steps within the time prescribed in the Compliance Response Plan, shall constitute a violation of the permit unless taking the response steps set forth in the Compliance Response Plan would be unreasonable.
- (c) After investigating the reason for the excursion, the Permittee is excused from taking further response steps for any of the following reasons:
- (1) The monitoring equipment malfunctioned, giving a false reading. This shall be an excuse from taking further response steps providing that prompt action was taken to correct the monitoring equipment.

- (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for an administrative amendment to the permit, and such request has not been denied or;
 - (3) An automatic measurement was taken when the process was not operating; or
 - (4) The process has already returned to operating within "normal" parameters and no response steps are required.
- (d) Records shall be kept of all instances in which the compliance related information was not met and of all response steps taken.

Record Keeping and Reporting Requirements

C.13 Malfunctions Report [326 IAC 1-6-2]

Pursuant to 326 IAC 1-6-2 (Records; Notice of Malfunction):

- (a) A record of all malfunctions, including startups or shutdowns of any facility or emission control equipment, which result in violations of applicable air pollution control regulations or applicable emission limitations shall be kept and retained for a period of three (3) years and shall be made available to the Indiana Department of Environmental Management (IDEM), Office of Air Quality(OAQ) or appointed representative upon request.
- (b) When a malfunction of any facility or emission control equipment occurs which lasts more than one (1) hour, said condition shall be reported to OAQ, using the Malfunction Report Forms (2 pages). Notification shall be made by telephone or facsimile, as soon as practicable, but in no event later than four (4) daytime business hours after the beginning of said occurrence.
- (c) Failure to report a malfunction of any emission control equipment shall constitute a violation of 326 IAC 1-6, and any other applicable rules. Information of the scope and expected duration of the malfunction shall be provided, including the items specified in 326 IAC 1-6-2(a)(1) through (6).
- (d) Malfunction is defined as any sudden, unavoidable failure of any air pollution control equipment, process, or combustion or process equipment to operate in a normal and usual manner. [326 IAC 1-2-39]

C.14 Monitoring Data Availability [326 IAC 2-6.1-2] [IC 13-14-1-13]

- (a) With the exception of performance tests conducted in accordance with Section C-Performance Testing, all observations, sampling, maintenance procedures, and record keeping, required as a condition of this permit shall be performed at all times the equipment is operating at normal representative conditions.
- (b) As an alternative to the observations, sampling, maintenance procedures, and record keeping of subsection (a) above, when the equipment listed in Section D of this permit is not operating, the Permittee shall either record the fact that the equipment is shut down or perform the observations, sampling, maintenance procedures, and record keeping that would otherwise be required by this permit.
- (c) If the equipment is operating but abnormal conditions prevail, additional observations and sampling should be taken with a record made of the nature of the abnormality.

- (d) If for reasons beyond its control, the operator fails to make required observations, sampling, maintenance procedures, or record keeping, reasons for this must be recorded.
- (e) At its discretion, IDEM may excuse such failure providing adequate justification is documented and such failures do not exceed five percent (5%) of the operating time in any quarter.
- (f) Temporary, unscheduled unavailability of staff qualified to perform the required observations, sampling, maintenance procedures, or record keeping shall be considered a valid reason for failure to perform the requirements stated in (a) above.

C.15 General Record Keeping Requirements [326 IAC 2-6.1-2]

- (a) Records of all required monitoring data and support information shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be kept at the source location for a minimum of three (3) years and available upon the request of an IDEM, OAQ, representative. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a written request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Records of required monitoring information shall include, where applicable:
 - (1) The date, place, and time of sampling or measurements;
 - (2) The dates analyses were performed;
 - (3) The company or entity performing the analyses;
 - (4) The analytic techniques or methods used;
 - (5) The results of such analyses; and
 - (6) The operating conditions existing at the time of sampling or measurement.
- (c) Support information shall include, where applicable:
 - (1) Copies of all reports required by this permit;
 - (2) All original strip chart recordings for continuous monitoring instrumentation;
 - (3) All calibration and maintenance records;
 - (4) Records of preventive maintenance shall be sufficient to demonstrate that failure to implement the Preventive Maintenance Plan did not cause or contribute to a violation of any limitation on emissions or potential to emit. To be relied upon subsequent to any such violation, these records may include, but are not limited to: work orders, parts inventories, and operator's standard operating procedures. Records of response steps taken shall indicate whether the response steps were performed in accordance with the Compliance Response Plan required by Section C - Compliance Monitoring Plan - Failure to take Response Steps, of this permit, and whether a deviation from a permit condition was reported. All records shall briefly describe what maintenance and response steps were taken and indicate who performed the tasks.

- (d) All record keeping requirements not already legally required shall be implemented when operation begins.

C.16 General Reporting Requirements [326 IAC 2-1.1-11] [326 IAC 2-6.1-2] [IC 13-14-1-13]

- (a) Reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

- (b) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (c) The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period.

C.17 Annual Notification [326 IAC 2-6.1-5(a)(5)]

- (a) Annual notification shall be submitted to the Office of Air Quality stating whether or not the source is in operation and in compliance with the terms and conditions contained in this permit.
- (b) Noncompliance with any condition must be specifically identified. If there are any permit conditions or requirements for which the source is not in compliance at any time during the year, the Permittee must provide a narrative description of how the source did or will achieve compliance and the date compliance was, or will be, achieved. The notification must be signed by an authorized individual.
- (c) The annual notice shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in the format attached no later than March 1 of each year to:

Compliance Data Section, Office of Air Quality
Indiana Department of Environmental Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, IN 46206-6015

- (d) The notification shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.

SECTION D.1

EMISSIONS UNIT OPERATION CONDITIONS

Facility Description:

- (a) One (1) paint booth equipped with four (4) air atomization spray guns used to paint mobile hydraulic lift equipment at a maximum capacity of 0.25 units per hour. Emissions are exhausted at four (4) stacks (identified as S-NW, S-NE, S-SW, and S-SE) with particulate matter controlled by four (4) dry filters.
- (b) One (1) assembly plant using organic solvent for hand wipe cleaning operations with maximum VOC emissions of 0.12 tons per year.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards

D.1.1 Volatile Organic Compounds (VOC) [326 IAC 8-2-9]

- (a) Pursuant to 326 IAC 8-2-9 (Miscellaneous Metal Coating Operations), the volume weighted average volatile organic compound (VOC) content of coating applied to metal parts of the hydraulic lift equipment shall be limited to 3.5 pounds of VOCs per gallon of coating less water, as delivered to the applicator for any calendar day, for air dried coatings.
- (b) Solvent sprayed from application equipment during cleanup or color changes shall be directed into containers. Such containers shall be closed as soon as such solvent spraying is complete, and the waste solvent shall be disposed of in such a manner that evaporation is minimized.

D.1.2 Particulate Matter (PM) [326 IAC 6-3-2(c)]

The PM from the shall not exceed the pound per hour emission rate established as E in the following formula:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$

where E = rate of emission in pounds per hour; and
P = process weight rate in tons per hour

D.1.3 Preventive Maintenance Plan [326 IAC 1-6-3]

A Preventive Maintenance Plan, in accordance with Section C - Preventive Maintenance Plan, of this permit, is required for this emissions unit and any control devices.

Compliance Determination Requirements

D.1.4 Testing Requirements [326 IAC 2-1.1-11]

The Permittee is not required to test this emissions unit by this permit. However, IDEM may require compliance testing when necessary to determine if the emissions unit is in compliance. If testing is required by IDEM, compliance with the PM limit specified in Condition D.1.2 shall be determined by a performance test conducted in accordance with Section C - Performance Testing.

D.1.5 Volatile Organic Compounds (VOC)

Compliance with the VOC content limitation contained in Condition D.1.1 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) using formulation data supplied by the

coating manufacturer. IDEM, OAQ, reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

D.1.6 Volatile Organic Compounds (VOC)

Pursuant to 326 IAC 8-1-2(a)(7), when volume weighted averaging of the coatings is used to determine compliance with the limitation set in Condition D.1.1. This volume weighted average shall be determined by the following equation:

$$A = [3 (C \times U) / 3 U]$$

Where: A is the volume weighted average in pounds VOC per gallon
C is the VOC content of the coating in pounds VOC per gallon, and
U is the usage rate of the coating in gallons per unit, hour, day or other unit of time.

Compliance Monitoring Requirements [326 IAC 2-5.1-3(e)(2)] [326 IAC 2-6.1-5(a)(2)]

D.1.7 Particulate Matter (PM)

The dry filters used for PM control shall be in operation at all times when the paint booth is in operation.

D.1.8 Monitoring

- (a) Daily inspections shall be performed to verify the placement, integrity and particle loading of the filters. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the surface coating booth stacks (S-NW, S-NE, S-SW, and S-SE) while the booth is in operation. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Monitoring Plan - Failure to Take Response Steps, shall be considered a violation of this permit.
- (b) Monthly inspections shall be performed of the coating emissions from the stack and the presence of overspray on the rooftops and the nearby ground. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when a noticeable change in overspray emission, or evidence of overspray emission is observed. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Monitoring Plan - Failure to Take Response Steps, shall be considered a violation of this permit.
- (c) Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plan.

Record Keeping and Reporting Requirements [326 IAC 2-5.1-3(e)(2)] [326 IAC 2-6.1-5(a)(2)]

D.1.9 Record Keeping Requirements

- (a) To document compliance with Conditions D.1.1 and D.1.2, the Permittee shall maintain records in accordance with (1) and (2) below. Records maintained for (1) and (2) shall be taken daily and shall be complete and sufficient to establish compliance with the VOC content limit established in Condition D.1.1.
 - (1) The VOC content of each coating material and solvent used. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used. Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents; and
 - (2) A log of the dates of use.

- (b) To document compliance with Condition D.1.8, the Permittee shall maintain a log of weekly overspray observations, daily and monthly inspections, and those additional inspections prescribed by the Preventive Maintenance Plan.
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE DATA SECTION**

**MINOR SOURCE OPERATING PERMIT
ANNUAL NOTIFICATION**

This form should be used to comply with the notification requirements under 326 IAC 2-6.1-5(a)(5).

Company Name:	MTI Insulated Products, Inc.
Address:	4419 Ardmore Avenue
City:	Ft. Wayne, Indiana 46899
Phone #:	219-479-4605
MSOP #:	003-13570-0037

I hereby certify that MTI Insulated Products, Inc. is

☒ still in operation.

☐ no longer in operation.

I hereby certify that MTI Insulated Products, Inc. is

☒ in compliance with the requirements of MSOP **003-13570-00037**.

☐ not in compliance with the requirements of MSOP **003-13570-00037**.

Authorized Individual (typed):
Title:
Signature:
Date:

If there are any conditions or requirements for which the source is not in compliance, provide a narrative description of how the source did or will achieve compliance and the date compliance was, or will be achieved.

Noncompliance:

MALFUNCTION REPORT

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY FAX NUMBER - 317 233-5967

**This form should only be used to report malfunctions applicable to Rule 326 IAC 1-6
and to qualify for the exemption under 326 IAC 1-6-4.**

THIS FACILITY MEETS THE APPLICABILITY REQUIREMENTS BECAUSE IT HAS POTENTIAL TO EMIT 25 TONS/YEAR PARTICULATE MATTER ?_____, 25 TONS/YEAR SULFUR DIOXIDE ?_____, 25 TONS/YEAR NITROGEN OXIDES?_____, 25 TONS/YEAR VOC ?_____, 25 TONS/YEAR HYDROGEN SULFIDE ?_____, 25 TONS/YEAR TOTAL REDUCED SULFUR ?_____, 25 TONS/YEAR REDUCED SULFUR COMPOUNDS ?_____, 25 TONS/YEAR FLUORIDES ?_____, 100TONS/YEAR CARBON MONOXIDE ?_____, 10 TONS/YEAR ANY SINGLE HAZARDOUS AIR POLLUTANT ?_____, 25 TONS/YEAR ANY COMBINATION HAZARDOUS AIR POLLUTANT ?_____, 1 TON/YEAR LEAD OR LEAD COMPOUNDS MEASURED AS ELEMENTAL LEAD ?_____, OR IS A SOURCE LISTED UNDER 326 IAC 2-5.1-3(2) ?_____. EMISSIONS FROM MALFUNCTIONING CONTROL EQUIPMENT OR PROCESS EQUIPMENT CAUSED EMISSIONS IN EXCESS OF APPLICABLE LIMITATION _____.

THIS MALFUNCTION RESULTED IN A VIOLATION OF: 326 IAC _____ OR, PERMIT CONDITION # _____ AND/OR PERMIT LIMIT OF _____

THIS INCIDENT MEETS THE DEFINITION OF 'MALFUNCTION' AS LISTED ON REVERSE SIDE ? Y N

THIS MALFUNCTION IS OR WILL BE LONGER THAN THE ONE (1) HOUR REPORTING REQUIREMENT ? Y N

COMPANY: _____ PHONE NO. () _____
LOCATION: (CITY AND COUNTY) _____
PERMIT NO. _____ AFS PLANT ID: _____ AFS POINT ID: _____ INSP: _____
CONTROL/PROCESS DEVICE WHICH MALFUNCTIONED AND REASON: _____

DATE/TIME MALFUNCTION STARTED: ____/____/20____ AM / PM

ESTIMATED HOURS OF OPERATION WITH MALFUNCTION CONDITION: _____

DATE/TIME CONTROL EQUIPMENT BACK-IN SERVICE ____/____/20____ AM/PM

TYPE OF POLLUTANTS EMITTED: TSP, PM-10, SO2, VOC, OTHER: _____

ESTIMATED AMOUNT OF POLLUTANT EMITTED DURING MALFUNCTION: _____

MEASURES TAKEN TO MINIMIZE EMISSIONS: _____

REASONS WHY FACILITY CANNOT BE SHUTDOWN DURING REPAIRS:

CONTINUED OPERATION REQUIRED TO PROVIDE ESSENTIAL* SERVICES: _____
CONTINUED OPERATION NECESSARY TO PREVENT INJURY TO PERSONS: _____
CONTINUED OPERATION NECESSARY TO PREVENT SEVERE DAMAGE TO EQUIPMENT: _____
INTERIM CONTROL MEASURES: (IF APPLICABLE) _____

MALFUNCTION REPORTED BY: _____ TITLE: _____
(SIGNATURE IF FAXED)

MALFUNCTION RECORDED BY: _____ DATE: _____ TIME: _____

*SEE PAGE 2

**Please note - This form should only be used to report malfunctions
applicable to Rule 326 IAC 1-6 and to qualify for
the exemption under 326 IAC 1-6-4.**

326 IAC 1-6-1 Applicability of rule

Sec. 1. This rule applies to the owner or operator of any facility required to obtain a permit under 326 IAC 2-5.1 or 326 IAC 2-6.1.

326 IAC 1-2-39 "Malfunction" definition

Sec. 39. Any sudden, unavoidable failure of any air pollution control equipment, process, or combustion or process equipment to operate in a normal and usual manner.

***Essential services** are interpreted to mean those operations, such as, the providing of electricity by power plants. Continued operation solely for the economic benefit of the owner or operator shall not be sufficient reason why a facility cannot be shutdown during a control equipment shutdown.

If this item is checked on the front, please explain rationale:

Mail to: Permit Administration & Development Section
Office of Air Quality
100 North Senate Avenue
P. O. Box 6015
Indianapolis, Indiana 46206-6015

MTI Insulated Products, Inc.
P.O. Box 9247
Ft. Wayne, Indiana 46809

Affidavit of Construction

I, _____, being duly sworn upon my oath, depose and say:
(Name of the Authorized Representative)

1. I live in _____ County, Indiana and being of sound mind and over twenty-one (21) years of age, I am competent to give this affidavit.
2. I hold the position of _____ for _____.
(Title) (Company Name)
3. By virtue of my position with _____, I have personal
(Company Name)
knowledge of the representations contained in this affidavit and am authorized to make
these representations on behalf of _____.
(Company Name)
4. I hereby certify that MTI Insulated Products, Inc., 4419 Ardmore Avenue, Ft. Wayne, Indiana, 46899,
completed construction of the paint booth on _____ in conformity with the requirements
and intent of the construction permit application received by the Office of Air Quality on November 30, 2000
and as permitted pursuant to **Construction Permit No. CP-003-13570, Plant ID No. 003-00037**
issued on _____
5. Additional (?operations/facilities) were constructed/substituted as described in the attachment to this
document and were not made in accordance with the construction permit. (Delete this statement if it
does not apply.)

Further Affiant said not.

I affirm under penalties of perjury that the representations contained in this affidavit are true, to the best of my information
and belief.

Signature

Date

STATE OF INDIANA)
)SS

COUNTY OF _____)

Subscribed and sworn to me, a notary public in and for _____ County and State of
Indiana on this _____ day of _____, 20 _____.
My Commission expires: _____

Signature

Name (typed or printed)

Section 10: Affidavit.wpd 7/00

Indiana Department of Environmental Management Office of Air Quality

Technical Support Document (TSD) for a New Source Construction and Minor Source Operating Permit

Source Background and Description

Source Name: MTI Insulated Products, Inc.
Source Location: 4419 Ardmore Avenue, Ft. Wayne, Indiana 46899
County: Allen
SIC Code: 3531
Operation Permit No.: 003-13570-00037
Permit Reviewer: ERG/AB

The Office of Air Quality (OAQ) has reviewed an application from MTI Insulated Products, Inc. relating to the construction and operation of a paint booth for painting hydraulic lift equipment.

Emission Units and Pollution Control Equipment

The source consists of the following permitted emission units and pollution control devices:

- (a) One (1) paint booth equipped with four (4) air atomization spray guns used to paint mobile hydraulic lift equipment at a maximum capacity of 0.25 units per hour. Emissions are exhausted at four (4) stacks (identified as S-NW, S-NE, S-SW, and S-SE) with particulate matter controlled by four (4) dry filters.
- (b) One (1) assembly plant using organic solvent for hand wipe cleaning operations with maximum VOC emissions of 0.12 tons per year.

Note: The assembly plant was exempt from permitting.

Unpermitted Emission Units and Pollution Control Equipment

There are no unpermitted facilities operating at this source during this review process.

Existing Approvals

No previous approvals have been issued to this source.

Source Definition

MTI Insulated Products, Inc. operates two (2) plants in Ft. Wayne, Indiana:

- (a) Plant 1 is located at 9733 Indianapolis Road, Ft. Wayne, Indiana 46809; and
- (b) Plant 2 is located at 4419 Ardmore Avenue, Ft. Wayne, Indiana 46808.

This permit is for Plant 2. Although both plants are owned and operated by the same company and operated under the same SIC code, the plants are located four miles apart and do not share the same employees or the same materials. Based on this information, IDEM, OAQ has determined that the plants are not considered as one source.

Stack Summary

Stack ID	Operation	Height (feet)	Diameter (feet)	Flow Rate (acfm)	Temperature (°F)
S-NW	Paint Booth	30	3.0	15,000	Ambient
S-NE	Paint Booth	30	3.0	15,000	Ambient
S-SW	Paint Booth	30	3.0	15,000	Ambient
S-SE	Paint Booth	30	3.0	15,000	Ambient

Enforcement Issue

There are no enforcement actions pending.

Recommendation

The staff recommends to the Commissioner that the construction and operation be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

A complete application for the purposes of this review was received on November 30, 2000.

Emission Calculations

See Appendix A of this document for detailed emissions calculations (pages 1 through 3).

Potential To Emit of Source or Revision Before Controls

Pursuant to 326 IAC 2-1.1-1(16), Potential to Emit is defined as “the maximum capacity of a stationary source or emissions unit to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or type or amount of material combusted, stored, or processed shall be treated as part of its design if the limitation is enforceable by the U. S. EPA, the department, or the appropriate local air pollution control agency.”

The potential emissions from the paint booth and the assembly plant cleaning operations are provided in the following tables:

Pollutant	Potential To Emit (tons/year)
PM	18.74
PM-10	18.74
SO ₂	0
VOC	26.9
CO	0
NO _x	0

HAP's	Potential To Emit (tons/year)
Xylene	2.75
Toluene	8.66
Methyl Ethyl ketone	1.72
Methanol	3.54
Hexamethylene Diisocyanate	0.01
TOTAL	16.7

- (a) The potential to emit (as defined in 326 IAC 2-7-1(29)) of all criteria pollutants are less than 100 tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-6.1.
- (b) The potential to emit (as defined in 326 IAC 2-7-1(29)) of any single HAP is less than ten (10) tons per year and potential to emit (as defined in 326 IAC 2-7-1(29)) of a combination HAPs is less than twenty-five (25) tons per year. Therefore, the source is not subject to the provisions of 326 IAC 2-7.

Limited Potential to Emit

The table below summarizes the potential to emit, reflecting all limits, of the significant emission units.

	Potential to Emit (tons/year)						
Process/facility	PM	PM-10	SO ₂	VOC	CO	NO _x	HAPs
Paint Booth	18.74	18.74	0	26.8	0	0	16.56
Assembly Area	0	0	0	0.1	0	0	0.12
Total Emissions	18.74	18.74	0	26.9	0	0	16.7

This new source is not a major stationary source because no attainment pollutant is emitted at a rate of 250 tons per year or greater and it is not in one of the 28 listed source categories. Therefore, pursuant to 326 IAC 2-2, and 40 CFR 52.21, the PSD requirements do not apply.

County Attainment Status

The source is located in Allen County.

Pollutant	Status
PM-10	Attainment
SO ₂	Attainment
NO ₂	Attainment
Ozone	Attainment
CO	Attainment
Lead	Attainment

- (a) Volatile organic compounds (VOC) and oxides of nitrogen (NO_x) are precursors for the formation of ozone. Therefore, VOC emissions are considered when evaluating the rule applicability relating to the ozone standards. Allen County has been designated as attainment or unclassifiable for ozone. Therefore, VOC and NO_x emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2 and 40 CFR 52.21.

- (b) Allen County has been classified as attainment or unclassifiable for all criteria pollutants. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2 and 40 CFR 52.21.

Part 70 Permit Determination

326 IAC 2-7 (Part 70 Permit Program)

This source is not subject to the Part 70 Permit requirements because the potential to emit (PTE) of:

- (a) each criteria pollutant is less than 100 tons per year,
- (b) a single hazardous air pollutant (HAP) is less than 10 tons per year, and
- (c) any combination of HAPs is less than 25 tons/year.

This is the first air approval issued to this source.

Federal Rule Applicability

- (a) There are no New Source Performance Standards (NSPS)(326 IAC 12 and 40 CFR Part 60) applicable to this source.
- (b) This source is not subject to the requirements of the New Source Performance Standard (NSPS), 40 CFR 60, Subpart MM - Standards of Performance for Automobile and Light Duty Truck Surface Coating Operations because this NSPS applies to prime coat, guide coat, and topcoat operations for automobile or light-duty trucks having gross weights less than 3,850 kg (8,500 lbs). The minimum gross weight for the MTI trucks is 15,000 lbs.
- (c) There are no National Emission Standards for Hazardous Air Pollutants (NESHAPs) (326 IAC 14 and 40 CFR Part 63) applicable to this source.

State Rule Applicability - Entire Source

326 IAC 2-6 (Emission Reporting)

This source is located in Allen County and the potential to emit VOC, PM₁₀, and NO_x is less than one (100) tons per year. Therefore, 326 IAC 2-6 does not apply.

326 IAC 5-1 (Visible Emissions Limitations)

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Exemptions), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings) as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor in a six (6) hour period.

State Rule Applicability - Individual Facilities

326 IAC 8-2-9 (Miscellaneous Metal Coating)

Pursuant to 326 IAC 8-2-9 (Miscellaneous Metal Coating Operations), the volatile organic compound (VOC) content of coating delivered to the applicator at the spray booth shall be limited to 3.5 pounds of VOCs per gallon of coating less water, for air dried coatings.

Solvent sprayed from application equipment during cleanup or color changes shall be directed into containers. Such containers shall be closed as soon as such solvent spraying is complete, and the waste solvent shall be disposed of in such a manner that evaporation is minimized.

This source is subject to 326 IAC 8-2-9 because the potential to emit VOCs is greater than 15 pounds per day.

Based on the MSDSs submitted by the source and calculations made, the spray booth is in compliance with this requirement. (Note that the coating (as applied) is a mixture of S-W white, hardener and accelerator, which are mixed in the proportions shown on Page 3 of the Appendix. Although some of the individual constituents of the coating have VOC contents greater than 3.5 lbs per gallon, the mixture has a VOC content of less than 3.5 lbs per gallon).

326 IAC 6-3-2 (Process Operations)

The particulate matter (PM) from the spray booth shall be limited by the following:

Interpolation and extrapolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour}$$

The dry filters shall be in operation at all times the paint booth is in operation, in order to comply with this limit.

326 IAC 8-2-2 (Automobile And Light Duty Truck Coating Operations)

This source is not subject to 326 IAC 8-2-2 (Automobile And Light Duty Truck Coating Operations) because the completed trucks have gross weights greater than 8,500 lbs and are not designed specifically for transportation.

Air Toxics Emissions

Indiana presently requests applicants to provide information on emissions of the 188 hazardous air pollutants (HAPs) set out in the Clean Air Act Amendments of 1990. These pollutants are either carcinogenic or otherwise considered toxic and are commonly used by industries. They are listed as air toxics on the Office of Air Quality (OAQ) Construction Permit Application Form Y.

- (a) This source will emit levels of air toxics less than those which constitute a major source according to Section 112 of the 1990 Clean Air Act Amendments.

Conclusion

The construction and operation of this paint booth shall be subject to the conditions of the attached proposed New Source Construction and Minor Source Operating Permit 003-13570-00037.

**Appendix A: Emissions Calculations
VOC and Particulate
From Surface Coating Operations**

Page 1 of 3 TSD App A

**Company Name: MTI Insulated Products, Inc.
Address City IN Zip: Ft. Wayne, IN 46899
CP: 003-13570-00037
Pit ID: 00037
Reviewer: ERG/AB
Date: 02/02/01**

Material	Density (Lb/Gal)	Weight % Volatile (H2O & Organics)	Weight % Water	Weight % Organics	Volume % Water	Volume % Non-Volatiles (solids)	Gal of Mat. (gal/unit)	Maximum (unit/hour)	Pounds VOC per gallon of coating less water	Pounds VOC per gallon of coating	Potential VOC pounds per hour	Potential VOC pounds per day	Potential VOC tons per year	Particulate Potential (ton/yr)	lb VOC/gal solids	Transfer Efficiency
S-W White	10.5	35.00%	0.0%	35.0%	0.0%	51.00%	3.00000	0.250	3.68	3.68	2.76	66.15	12.07	14.12	7.21	37%
Hardener	8.9	25.00%	0.0%	25.0%	0.0%	65.00%	1.00000	0.250	2.23	2.23	0.56	13.38	2.44	4.62	3.43	37%
Accelerator	8.1	98.80%	0.0%	98.8%	0.0%	5.00%	0.06250	0.250	8.03	8.03	0.13	3.01	0.55	0.00	160.65	37%
Cleanup Solvent (Paint Booth)	7.1	75.00%	0.0%	75.0%	0.0%	0.00%	2.00000	0.250	5.35	5.35	2.67	64.17	11.71	0.00	ERR	0%
Cleanup Solvent (Assembly Plant)	7.1	75.00%	0.0%	75.0%	0.0%	0.00%	0.01600	0.250	5.35	5.35	0.02	0.51	0.09	0.03	ERR	0%
	0.0	0.00%	0.0%	0.0%	0.0%	0.00%	0.00000	0.000	0.00	0.00	0.00	0.00	0.00	0.00	ERR	0%
	0.0	0.00%	0.0%	0.0%	0.0%	0.00%	0.00000	0.000	0.00	0.00	0.00	0.00	0.00	0.00	ERR	0%
	0.0	0.00%	0.0%	0.0%	0.0%	0.00%	0.00000	0.000	0.00	0.00	0.00	0.00	0.00	0.00	ERR	0%
	0.0	0.00%	0.0%	0.0%	0.0%	0.00%	0.00000	0.000	0.00	0.00	0.00	0.00	0.00	0.00	ERR	0%
	0.0	0.00%	0.0%	0.0%	0.0%	0.00%	0.00000	0.000	0.00	0.00	0.00	0.00	0.00	0.00	ERR	0%
	0.0	0.00%	0.0%	0.0%	0.0%	0.00%	0.00000	0.000	0.00	0.00	0.00	0.00	0.00	0.00	ERR	0%

Potential Emissions	6.13	147.23	26.87	18.78
----------------------------	-------------	---------------	--------------	--------------

METHODOLOGY

Note: Finish coat, hardener, and accelerator are mixed prior to application. See page 3 of this Appendix for calculation of VOC content as applied.

Pounds of VOC per Gallon Coating less Water = (Density (lb/gal) * Weight % Organics) / (1-Volume % water)

Pounds of VOC per Gallon Coating = (Density (lb/gal) * Weight % Organics)

Potential VOC Pounds per Hour = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr)

Potential VOC Pounds per Day = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (24 hr/day)

Potential VOC Tons per Year = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (8760 hr/yr) * (1 ton/2000 lbs)

Particulate Potential Tons per Year = (units/hour) * (gal/unit) * (lbs/gal) * (1- Weight % Volatiles) * (1-Transfer efficiency) *(8760 hrs/yr) *(1 ton/2000 lbs)

Pounds VOC per Gallon of Solids = (Density (lbs/gal) * Weight % organics) / (Volume % solids)

Total = Worst Coating + Sum of all solvents used

surcoat.wk4 9/95

Appendix A: Emission Calculations
HAP Emission Calculations

Page 2 of 3 TSD App A

Company Name: MTI Insulated Products, Inc.
Address City IN Zip: Ft. Wayne, IN 46899
CP#: 003-13570-00037
Plt ID: 00037
Permit Reviewer: ERG/AB
Date: 02/02/01

Material	Density (Lb/Gal)	Gallons of Material (gal/unit)	Maximum (unit/hour)	Weight % Xylene	Weight % Toluene	Weight % MEK	Weight % Methanol	Weight % HMDI	Xylene Emissions (ton/yr)	Toluene Emissions (ton/yr)	MEK Emissions (ton/yr)	Methanol Emissions (ton/yr)	HMDI Emissions (ton/yr)
S-W White	10.5	3.000000	0.25	0.00%	0.00%	5.00%	0.00%	0.00%	0.00	0.00	1.72	0.00	0.00
Hardener	8.92	1.000000	0.25	0.00%	0.00%	0.00%	0.00%	0.10%	0.00	0.00	0.00	0.00	0.01
Accelerator	8.13	0.062500	0.25	0.00%	0.00%	0.00%	0.00%	0.00%	0.00	0.00	0.00	0.00	0.00
Cleanup Solvent (Paint Booth)	7.13	2.000000	0.25	17.50%	55.00%	0.00%	22.50%	0.00%	2.73	8.59	0.00	3.51	0.00
Cleanup Solvent (Assembly Plant)	7.13	0.016000	0.25	17.50%	55.00%	0.00%	22.50%	0.00%	0.02	0.07	0.00	0.03	0.00

Total Potential Emissions									2.75	8.66	1.72	3.54	0.01
---------------------------	--	--	--	--	--	--	--	--	-------------	-------------	-------------	-------------	-------------

METHODOLOGY

HAPS emission rate (tons/yr) = Density (lb/gal) * Gal of Material (gal/unit) * Maximum (unit/hr) * Weight % HAP * 8760 hrs/yr * 1 ton/2000 lbs

**Appendix A: Emission Calculations
VOC Content of Paint (As Applied)**

**Company Name: MTI Insulated Products, Inc.
Address City IN Zip: Ft. Wayne, IN 46899
CP#: 003-13570-00037
Plt ID: 00037
Permit Reviewer: ERG/AB
Date: 02/02/01**

Paint Constituents	Density (lbs/gal)	VOC Content of Material (% wt)	Volume Used (gal)	Mass Used (lbs)	Mass of VOC Used (lbs)
S-W White	10.5	35	3	31.5	11.025
Hardener	8.92	25	1	8.92	2.23
Accelerator	8.13	98.8	0.06	0.51	0.50
Totals			4.06	40.93	13.76

**Since S-W White, hardener, and accelerator are mixed prior to application, the
VOC Content of the Paint as Applied is :**

VOC Concentration in Paint = 13.75 lbs of VOC/ 4.06 gallons of paint **3.39 lbs of VOC/gal of paint**

**Since 3.39 lbs of VOC per gallon of paint (as applied) is less than the 3.5 lbs VOC per gallon limit, the paint will be
in compliance with 326 IAC 6-2-9 Miscellaneous Metal Coating Operations.**